

Creamsource Mini+



Creamsource is a High Power LED luminaire designed for the Film and Television industries. Equally comfortable on location or in the studio, Creamsource is a truly versatile lighting tool.

With all the same features as the popular Creamsource Doppio+ in a compact 1x1 form factor, the Creamsource Mini+ is ideal for location or OB work.

A large output area creates the unique quality of 'wrapping' your subject in soft light, while the powerful LED engine provides intensity and throw to rival a small HMI fixture. Only Creamsource can provide this mix of light properties in such a small form factor.

Precision optics provide a consistent beam with naturally soft edges, while a wide selection of light control tools are available to shape and cut the beam to achieve exactly the look you require.

With exceptional build quality, it has been engineered for years of reliable service. Little wonder Creamsource is becoming an industry standard for lighting professionals around the world.

All units are supplied with the following:

- > Standard yoke for mounting on stand
- > AC Power Supply, 160W capacity, 90-250V auto-ranging
- > 3m Power header cable
- > 1 Medium diffusion lens
- > 1 Empty gel frame
- > IEC power cable for your country

Product Specifications

CRI	Typical 95, minimum 90
TLCI	Typical 95, minimum 90
Beam Angle, SPOT Lens	13° (Half Peak Angle)
Tilt Angle	170° (Up), 80° (Down)
Mounting	28mm Spigot, 5/8th Socket Adapter
Yoke	Removable (Quick Release System). Pole Operated Yoke Available on Request
Filter Rails	2 Filter Rails for Secondary Lenses and Gels
User interface	High Precision Digital Rotary Encoder, 4 Button Keypad, Graphic LCD Display
Control	On-Board Interface, 5 Pin DMX In and Thru, Wired Remote Control
Dimming	0-100%, Continuous
High Speed Capability	Over 1000fps Flicker Free in High Speed Mode
Synchronization	Sync Input for Triggering and Syncing to Camera Shutter
Max Ambient Temperature	40°C
Cooling	Passive (Silent) Under Normal Conditions. Low Noise Back-Up Fans
Estimated LED Lifespan	50,000hrs
Input (Fixture)	24-32V DC, Max 6.3A, 150W
Input (Power Supply)	90-260V AC, 50-60Hz, Max 2.0A
Protection Class	IP20
Weight	5.2kg / 11.4lbs (Including Yoke)
Dimensions	392 x 455 x 100mm / 14.7" x 15.4" x 4" (Including Yoke) 307 x 332 x 100mm / 12.5" x 13.4" x 4" (Including Yoke)
Warranty	2 Years on Fixtures, 12 Months on Accessories
Certifications	CE, FCC, C-Tick. Pending: ETL, CSA

Creamsource Mini+

Daylight



Temperature:
5600K
Power: 150W

Order Number Description
K-CSM-2-D-ESS, SPOT Lenses
Kit includes: CSM-FRAME CSM-PSU-160
CSM-PWR-5M CSM-LENS-M
CSM-YOKE

PHOTOMETRIC DATA

	1m / 3.3ft	2m / 6.6ft	3m / 9.8ft	4m / 13.1ft
5600K	80,300 lx / 7,460fc	34,500 lx / 3,210 fc	17,500 lx / 1,630 fc	10,200 lx / 950 fc

Bender



Temperature:
between
2700K - 6500K
Power: 150W

Order Number Description
K-CSM-2-B-ESS, SPOT Lenses
Kit includes: CSM-FRAME CSM-PSU-160
CSM-PWR-5M CSM-LENS-M
CSM-YOKE

PHOTOMETRIC DATA

	1m / 3.3ft	2m / 6.6ft	3m / 9.8ft	4m / 13.1ft
3200K	41,900 lx / 3,900 fc	17,400 lx / 1,620 fc	8,830 lx / 830 fc	5,170 lx / 490 fc
4000K	69,900lx / 6,500 fc	29,400 lx / 2,740 fc	15,000 lx / 1,400 fc	8,800 lx / 820 fc
5600K	44,100 lx / 4,100 fc	18,900lx / 1,760 fc	9,730 lx / 910 fc	5,700lx / 530 fc

Kits

PRO KIT



Includes:
Softbox & Carry Bag

K-CSM-2-D-PRO Creamsource Mini+ Daylight High CRI Pro Kit

K-CSM-2-B-PRO Creamsource Mini+ Bender High CRI Pro Kit

GAFFER KIT



Includes:
Same as Pro with remote, snapbag and battery mount kit.

K-CSM-2-D-GAF-V Creamsource Mini+ Daylight High CRI Gaffer Kit (V-Lock)

K-CSM-2-D-GAF-A Creamsource Mini+ Daylight High CRI Gaffer Kit (AB Mount)

K-CSM-2-B-GAF-V Creamsource Mini+ Bender High CRI Gaffer Kit (V-Lock)

K-CSM-2-B-GAF-A Creamsource Mini+ Bender High CRI Gaffer Kit (AB Mount)

Accessories

CSM-BAG	Softbag Padded Case with Rigid Internal Shell
CSM-BARNDOOR	Barn Doors
CSM-FRAME	Gel-Frame (Empty)
CSM-LENS-M	Medium Angle Drop-In Lens, 30°
CSM-LENS-W	Wide Angle Drop-In Lens, 60°
CSM-MOUNT-V	Dual V-Lock Battery Mounting Plate
CSM-MOUNT-AB	Dual Anton Bauer Battery Mounting Plate
CSM-MOUNT-PSU-160	Rear Mounting Plate for Power Supply
CSM-POLE-YOKE	Pole Operated Yoke Upgrade
CSM-PWR-3M	Power Supply Lead 5M
CS-REM	Creamtwist Wired Remote Controller
CS-REM-EXT-10M	Creamtwist Remote Extension Lead 10M
CSM-SNAPBAG	DopChoice Snap-Bag Softbox
CS-SYNC	Flashbandit Camera Sync Adapter
CSM-SNAPGRID-40	Creamsource Mini+ Snap Grid 40 degree (to fit SnapBag)



creamsource

Outsight Pty Ltd

6/888 Bourke St, Zetland
Sydney NSW 2017, AUSTRALIA

TEL (SYD): +61 2 8005 1288 (Sales Hotline)

TEL (USA): +1 818 748 8401 (Sales Hotline)

TEL (SYD): +61 2 9669 6681 (Head Office)

sales@outsight.com.au | www.outsight.com.au